Cleaning and Care

| | LAFFEL | SURFACES | | | |
|--|--|--|--|--|--|
| CLEANING CEMENT-BASED GROUT AFTER INSTALLATION | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | | TILE CLEANER | FABER CHIMICA | | |
| | Acid detergent | FILA CLEANER | FILA | | |
| | | FLOOR CLEANER | FABER CHIMICA | | |
| PROCEDURE * | Residues of cement-based grouts containing resin or latex must be removed immediately with a sponge. Rinse with plenty of water. Wash with a mil acid or neutral cleaning solution, diluted in water as indicated by the manufacturer. Rub vigorously with a motorised brush or broom. Rinse thoroughly with clean water. Soak up liquid with a rubber-coated squeegee, clean cloths or liquid remover. Repeat cleaning and rinse twi with clean water. Allow to dry. | | | | |
| CLEANING EPOXY-BASED GROUT AFTER INSTALLATION | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Alkaline detergent | EPOXY REMOVER | FABER CHIMICA | | |
| | | FILA CR 10 | FILA | | |
| PROCEDURE * | Epoxy-based grout must be removed immediately with a sponge. Rinse with plenty of water. The day of grouting, wash the floor with an alkaling detergent, diluted as indicated by the manufacturer. Rub vigorously with a motorised brush or broom. Rinse thoroughly with clean water. Soak up liquid with a rubber-coated squeegee, clean cloths or liquid remover. Repeat cleaning and rinse twice with clean water. Allow to dry. If grout stains remain, use a suitable solvent, such as a nitro thinner. | | | | |
| RECOMMENDED CLEANING BEFORE FURNISHING ROOMS | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Mildly acid or neutral detergent | TILE CLEANER | FABER CHIMICA | | |
| | | FILA CLEANER | FILA | | |
| | | FLOOR CLEANER | FABER CHIMICA | | |
| PROCEDURE * | Wash the floor with a mildly acid or neutral cleaning solution, diluted in water as indicated by the manufacturer. Rub vigorously with a motorised bru or broom. Rinse thoroughly with clean water. Soak up liquid with a rubber-coated squeegee, clean cloths or liquid remover. Repeat cleaning and rinse twi with clean water. Allow to dry. | | | | |
| ROUTINE CARE | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Neutral detergent | FILA CLEANER | FILA | | |
| | | FLOOR CLEANER | FABER CHIMICA | | |
| PROCEDURE * | Wash the floor with a neutral detergent, diluted in water as indicated by the manufacturer. Never use wax-based products or glossenhancers. Rinse thoroughly with clean water and allow to dry. | | | | |
| REMOVAL OF COLOURED STAINS (wine, fruit, coffee, nicotine | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| wille, Hult, conee, nicotine | Multipurpose detergent | COLORED STAIN REMOVER | FABER CHIMICA | | |
| wine, iruit, conee, nicotine | Multipurpose detergent | | | | |
| wine, nuit, conee, nicotine | Multipurpose detergent | PS 87 | FILA | | |
| | | | FILA cated by the manufacturer. Then rinse the surface. If the | | |
| PROCEDURE * | Apply directly to the stain and allow to soal | | | | |
| PROCEDURE * REMOVAL OF GREASY SUBSTANCES | Apply directly to the stain and allow to soal remains, repeat. | k, for the time and in the concentration indic | cated by the manufacturer. Then rinse the surface. If the | | |

* TEST THE PRODUCTS ON A SMALL AREA OF THE FLOOR

| | NATURAL AND TE | XTURED SURFACES | | | |
|--|---|--|--|--|--|
| CLEANING CEMENT-BASED GROUT AFTER INSTALLATION | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | | CEMENT REMOVER | FABER CHIMICA | | |
| | Acid detergent | KERANET | MAPEI | | |
| | | DETERDEK | FILA | | |
| PROCEDURE * | Residues of cement-based grouts containing resin or latex must be removed immediately with a sponge. Rinse with plenty of water. To remove hardened grout (within 7 days fi installation), use an acid detergent for after-installation cleaning, diluted in water in accordance to the manufacturer's instructions. Apply and rub with a motorised brush or br Rinse thoroughly with clean water. Soak up liquid with a rubber-coated squeegee, clean cloths or liquid remover. Repeat cleaning and rinse twice with clean water. Allow to dr. | | | | |
| CLEANING EPOXY-BASED GROUT AFTER INSTALLATION | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Alkaline detergent | EPOXY REMOVER | FABER CHIMICA | | |
| | | FILA CR 10 | FILA | | |
| PROCEDURE * | Wash the floor with a mildly acid or neutral cleaning solution, diluted in water as indicated by the manufacturer. Rub vigorously with a motorised brush or broom. Rinse thoroughly with clean water. Soak up liquid with a rubber-coated squeegee, clean cloths or liquid remover. Repeat cleaning and rinse twice with clean water. Allow to dry | | | | |
| ROUTINE CARE | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Neutral detergent | FILA CLEANER | FILA | | |
| | | FLOOR CLEANER | FABER CHIMICA | | |
| PROCEDURE * | Wash the floor with a neutral detergent, diluted in water as indicated by the manufacturer. Never use wax-based products or gloss-enhancers. Rinse thoroughly with clean wat and allow to dry. | | | | |
| REMOVAL OF COLOURED STAINS (wine, fruit, coffee, nicotine | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Multipurpose detergent | COLORED STAIN REMOVER | FABER CHIMICA | | |
| | | PS 87 | FILA | | |
| PROCEDURE * | Apply directly to the stain and allow to soak, for the time and in the concentration indicated by the manufacturer. Rinse thoroughly with clean water. If the stain remains, repeat | | | | |
| REMOVING GLOSSY / MATT MARK | TYPE OF DETERGENT | PRODUCT | MANUFACTURER | | |
| | Multipurpose detergent | TILE CLEANER | FABER CHIMICA | | |
| | | PS 87 | FILA | | |
| PROCEDURE * | Apply directly to the stain and allow to soak, for the t | ime and in the concentration indicated by the manufa | acturer. Remove residue with a moist sponge. If the stain remains, rep | | |

If <u>dirt residue cannot be removed</u> using standard detergents, refer to the following table:

| 11 <u>0</u> 1 | using stand | dard detergents, refer to the following table | - | | | |
|---|---|---|---|--|--|--|
| TYPE OF DIRT | SOLUTION | DETERGENTS | MANUFACTURER | | | |
| INORGANIC STAINS | | | | | | |
| coal, lime efflorescence, plaster, metallic marks, rust, pencil (graphite), natural paints. | ACID | DETERDEK CEMENT REMOVER | Fila Industria Chimica S.p.A. Faber Chimica | | | |
| ORGANIC STAINS | | | | | | |
| traces of rubber (soles of shoes, tyres) | ALKALINE | FILA PS/87 TILE CLEANER | Fila Industria Chimica S.p.A. Faber Chimica | | | |
| coca cola, coffee, wine, beer, ice-cream, animal and vegetable oils and fats, mustard, ketchup, mayonnaise, jam, hair dye, shampoo, lipstick, chewing-gum, marker pen ink | ALKALINE | FILA PS/87 TILE CLEANER | Fila Industria Chimica S.p.A. Faber Chimica | | | |
| SYNTHETIC STAINS | | | | | | |
| silicone and machine oils, silicone, resins, varnish, lacquer, bitumen, candle wax, paint, tar, india rubber, adhesive tape residues | SOLVENT | FILASOLV ACETONE DILUENTE NITRO | Fila Industria Chimica S.p.A. In Commercio In Commercio | | | |
| | SPECIFIC | CASES | | | | |
| TYPE OF DIRT | DETERGENTS | CLEANING METHOD | | | | |
| | SPECIFIC | STAINS | | | | |
| rimozione di cere protettive | DETERDEK (Fila) TILE CLEANER (Faber) | For the elimination of wax residues use acid cleaning, scrubbing vigorously with a scotch-brite buffer until complete remov the solid material. If silicone haloes remain, apply flasolv, leaving it to act until it has completely evaporated. Rinse thoroughly with hot, clean water. | | | | |
| alonature rotonde delle ventose | FILA HOBBY (Fila) PS/87 (Fila) | Use the specific nozzle (for fila hobby) to spray the detergent onto the marked tile and leave to act for a few seconds (never unt completely dry). Scrub vigorously with a damp scotch-brite buffer and rinse thoroughly with hot, clean water. | | | | |
| | MACCHIE RE | ESISTENTI | | | | |
| rimozione di cere protettive | PH ZERO (Fila Industria Chimica) | Ph zero is a stronger acid than deterdek and therefore has a more aggressive action against inorganic stains. Only for use in cases which are deemed to be extreme, after trying repeatedly with deterdek. | | | | |
| alonature rotonde delle ventose | DRASTIC (Fila Industria Chimica) | Drastic is a stronger alkaline product than ps/87 and so has a more aggressive action against organic stains. Only for use in cases which are deemed to be extreme, after trying repeatedly with ps/87. | | | | |
| Jotornont manufacturors: FII ∆ (Padoua): Tol. ±39 049 9467 | 300 - Fay +39 049 9460753 - fila@filachim it - www.filachim | com - FARER CHIMICA s.r.l. (Ancona): Tel. +39.073.2627178 | - Fax ±39 073 222935 - www.faherchimica.com | | | |

Detergent manufacturers: FILA (Padova): Tel. +39 049 9467300 - Fax +39 049 946753 - fila@filachim.it - www.filachim.com - FABER CHIMICA s.r.l. (Ancona): Tel. +39 073 2627178 - Fax +39 073 222935 - www.faberchimica.com